

M A T E R I A L S A F E T Y D A T A S H E E T

PRODUCT NAME: AERO PREP SURFACE CLEANER
PRODUCT CODE: 271

HMIS CODES: H F R P
2*4 0 X

SECTION I - MANUFACTURER IDENTIFICATION

MANUFACTURER'S NAME: PACIFIC COAST LACQUER
ADDRESS : 3150 E. PICO BLVD.
LOS ANGELES, CA 90023-3683
EMERGENCY PHONE(CHEMTREC) : (800) 424-9300 DATE PRINTED : 07/26/06
INFORMATION PHONE : (800) 672-4900 NAME OF PREPARER : N/A

SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION

Table with 5 columns: REPORTABLE COMPONENTS, CAS NUMBER, VAPOR PRESSURE mmHG, @TEMP(F), WEIGHT PERCENT. Rows include VM&P NAPHTHA, PROPANE, ISOBUTANE, ISOPROPYL ALCOHOL, 2-PROPANOL, and NORMAL BUTANE.

~Indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING RANGE (Deg F): 140 - 260 DENSITY: 5.91 lb/gl
VAPOR DENSITY: HEAVIER THAN AIR SPECIFIC GRAVITY (H2O=1): 0.71
COATING V.O.C.: 5.62 lb/gl MATERIAL V.O.C.: 5.62 lb/gl
COATING V.O.C.: 673 g/l MATERIAL V.O.C.: 673 g/l
SOLUBILITY IN WATER: Negligible EVAPORATION RATE: SLOWER THAN ETHER
FASTER THAN n-BUTYL ACETATE
APPEARANCE AND ODOR: Clear liquid with solvent odor.

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (Deg F): <1 METHOD USED: TCC
FLAMMABLE LIMITS IN AIR BY % VOLUME- LOWER: 1 UPPER: 12

EXTINGUISHING MEDIA: FOAM, CO2, DRY CHEMICAL

SPECIAL FIREFIGHTING PROCEDURES
Contents are under pressure. Water spray may be used to cool containers exposed to heat or fire to prevent pressure build up.

UNUSUAL FIRE AND EXPLOSION HAZARDS
Aerosol spray is EXTREMELY FLAMMABLE. Closed containers may explode due to build up of pressure from extreme heat or fire. Do not puncture. Vapors may be sensitive to static charge.

Flammability = T.D.G.R. Class ORM-D Consumer Commodity, (UN1950 CLASS 9), NFPA 30B, Level 3 Aerosol

=====
SECTION V - REACTIVITY DATA
=====

STABILITY: STABLE

CONDITIONS TO AVOID

Avoid heat, sparks and open flame

INCOMPATIBILITY (MATERIALS TO AVOID)

Strong oxidizing agents

HAZARDOUS DECOMPOSITION OR BYPRODUCTS

Thermal decomposition may yield carbon dioxide and/or carbon monoxide.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

=====
SECTION VI - HEALTH HAZARD DATA
=====

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Inhalation: May cause irritation to nose, eyes and respiratory tract. High vapor concentrations may cause CNS depression

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Skin and eye contact: Redness and itching or burning sensation may indicate eye or excessive skin exposure.

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Skin absorption: May cause skin irritation.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Ingestion: Maybe harmful if swallowed.

HEALTH HAZARDS (ACUTE AND CHRONIC)

Acute: In a confined area, vapors in high concentration are anesthetic. May cause eye, skin and respiratory irritation, light-headedness, giddiness and nausea. Chronic: Repeated and prolonged overexposure to solvents may cause brain and nervous system damage.

CARCINOGENICITY: NTP CARCINOGEN: No IARC MONOGRAPHS: No OSHA REGULATED: No

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

Pre-existing eye, skin and respiratory disorders may be aggravated.

EMERGENCY AND FIRST AID PROCEDURES

INHALATION: REMOVE TO FRESH AIR. APPLY ARTIFICIAL RESPIRATION IF NECESSARY.

SPLASH (EYES): FLUSH EYES IMMEDIATELY WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. SPLASH (SKIN): WASH AFFECTED AREAS WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING. INGESTION: GET MEDICAL ATTENTION IMMEDIATELY.

=====
SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE
=====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

PROVIDE VENTILATION. ABSORB WITH INERT MATERIAL AND PLACE IN A CLOSED CONTAINER. WEAR PROTECTIVE CLOTHING DURING CLEANUP. ELIMINATE ALL SOURCES OF IGNITION. FLUSH HEAVILY WITH WATER.

WASTE DISPOSAL METHOD

Waste must be disposed of in accordance with federal, state and local environmental control regulations. Incineration is the preferred method. Empty containers must be handled with care due to product residue and flammable solvent vapor. Decontaminate containers prior to disposal. DO NOT HEAT OR CUT

EMPTY CONTAINER WITH ELECTRIC OR GAS TORCH.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Do not store above 120 Deg F. Keep at room temperature.

OTHER PRECAUTIONS

Do not get in eyes. Do not breathe vapors. Avoid skin contact. Do not take internally. Smoking while using this product must be strickly prohibited.

===== SECTION VIII - CONTROL MEASURES =====

VENTILATION

Use explosion-proof ventilation as required to control vapor concentrations.

RESPIRATORY PROTECTION

Use a NIOSH-approved respirator if exposure exceeds TLV limits. Follow OSHA regulation 29CFR 1910.134 for respirator use. Use air-purifying respirator that respirator supplier has demonstrated to be effective for solvent vapors when concentrations exceed the TLV up to the maximum level at which the respirator is effective. If the concentration of solvents is not known, use positive pressure air-supplied respirator.

PROTECTIVE GLOVES

Chemical resistant gloves

EYE PROTECTION

Safety glasses with unperforated sideshields.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT

Impermeable apron, eye bath and safety shower

WORK/HYGIENIC PRACTICES

Wash hands thoroughly before eating or using the washroom. Smoke in smoking areas only.

===== SECTION IX - REGULATORY INFORMATION =====

CALIFORNIA PROPOSITION 65

None

===== SECTION X - DISCLAIMER =====

The information contained herein is based on the data available to us and is believed to be correct. However, Pacific Coast Lacquer Co. makes no warranty expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof. Pacific Coast Lacquer Co. assumes no responsibility for injury from the use of the product described herein.