





## EMERGENCY AND FIRST AID PROCEDURES

INHALATION: REMOVE TO FRESH AIR AND PROVIDE OXYGEN IF BREATHING IS DIFFICULT. SPLASH (EYES): FLUSH EYES IMMEDIATELY WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. SPLASH (SKIN): WASH AFFECTED AREAS WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING. INGESTION: DO NOT INDUCE VOMITING. IF VOMITING OCCURS SPONTANEOUSLY, KEEP HEAD BELOW HIPS TO PREVENT ASPIRATION OF LIQUID INTO THE LUNGS. GET MEDICAL ATTENTION IMMEDIATELY.

## ===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

## STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

REMOVE ALL SOURCES OF IGNITION AND PROVIDE VENTILATION. LARGE SPILLS MAY BE PUMPED TO SALVAGE VESSELS. SMALL SPILLS MAY BE PICKED UP WITH AN ABSORBENT MATERIAL.

## WASTE DISPOSAL METHOD

Place in tightly closed containers and dispose of in accordance with local, state and federal regulations.

## PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Keep away from heat, sparks and open flames. Keep containers closed when not in use. Use with adequate ventilation.

## OTHER PRECAUTIONS

Do not take internally. Ground equipment to prevent accumulation of static charge. Do not cut, weld, drill or grind on or near containers.

## ===== SECTION VIII - CONTROL MEASURES =====

## RESPIRATORY PROTECTION

Use self-contained breathing apparatus where vapor concentration may be above TLV limits. Where vapor does not exceed TLV limits, use NIOSH/MSHA approved respirator.

## VENTILATION

Use explosion-proof ventilation as required to control vapor concentrations.

## PROTECTIVE GLOVES

Chemical resistant gloves

## EYE PROTECTION

Safety glasses, splash goggles or face shield. Contact lenses should not be worn.

## OTHER PROTECTIVE CLOTHING OR EQUIPMENT

Safety showers and eyewash stations should be provided.

## WORK/HYGIENIC PRACTICES

Wash hands thoroughly before eating or using the washroom. Smoke in smoking areas only.

## ===== SECTION IX - TRANSPORT INFORMATION =====

## DOT (GROUND)

1.3 gallons (5 liters) or less:

UN1263, Paint Related Materials, 3, PGII, "Ltd. Qty."

Greater than 1.3 gallons (5 liters):

UN1263, Paint Related Materials, 3, PGII

AIR

UN1263, Paint Related Materials, 3, PGII

===== SECTION X - REGULATORY INFORMATION =====

CALIFORNIA PROPOSITION 65

This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

Contains: Toluene -

This product contains a chemical known to the State of California to cause cancer.

Contains: Ethylbenzene -

===== SECTION XI - DISCLAIMER =====

The information contained herein is based on the data available to us and is believed to be correct. However, PCL makes no warranty expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof. PCL assumes no responsibility for injury from the use of the product described herein.