

M A T E R I A L S A F E T Y D A T A S H E E T

PRODUCT NAME: 2K EPOXY PRIME-N-SEAL GRAY - PART A
PRODUCT CODE: 6701

HMIS CODES: H F R P
2*3 2

=====
SECTION I - MANUFACTURER IDENTIFICATION
=====

MANUFACTURER'S NAME: PACIFIC COAST LACQUER
ADDRESS : 3150 E. PICO BLVD.

LOS ANGELES, CA 90023-3683

EMERGENCY PHONE(CHEMTREC) : (800) 424-9300 DATE PRINTED : 2/14/2008
INFORMATION PHONE : (800) 672-4900 NAME OF PREPARER :

=====
SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION
=====

| REPORTABLE COMPONENTS | CAS NUMBER | VAPOR PRESSURE mmHG | @TEMP(F) | WEIGHT PERCENT |
|--|-------------|------------------------|----------|-------------------|
| ACETONE | 67-64-1 | 185.5 | 68 | 16 |
| OSHA PEL: 1000 ppm; 2,400 mg/m3 | | | | |
| OSHA TWA: 750 ppm; 1,800 mg/m3 | | | | |
| OSHA STEL: 1000 ppm; 2,400 mg/m3 | | | | |
| ACGIH TWA: 500 ppm, STEL: 750 ppm | | | | |
| ~ PARACHLOROBENZOTRIFLUORIDE | 98-56-6 | 5.3 | 68 | 3.92 |
| OSHA PEL: NE, ACGIH TLV: NE | | | | |
| ~ XYLENE (MIXED ISOMERS) | 1330-20-7 | 6.1 | 68 | 3.65 |
| OSHA PEL: 100 ppm, ACGIH TLV: 100 ppm | | | | |
| ~ GYLCIDOXYPROPYL TRIMETHOXYSILANE | 002530-83-8 | NA | | 2.45 |
| METHYL AMYL KETONE , 2-HEPTANONE | 110-43-0 | 2.14 | 68 | 2 |
| ACGIH TLV: 50 ppm | | | | |
| ~ ETHYL BENZENE | 100-41-4 | 10 | 68 | 1.22 |
| OSHA PEL: 100 ppm, ACGIH TLV: 100 ppm | | | | |
| CARBON BLACK(as unbound particles of carbon) | 1333-86-4 | NA | NA | 1.0 |
| ACGIH TLV: 3.5 mg/m3 | | | | |
| ~ n-BUTYL ALCOHOL | 71-36-3 | 4.1 | 68 | .49 |
| OSHA PEL: 50 ppm, ACGIH TLV: 50 ppm | | | | |

~Indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.

=====
SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS
=====

| | |
|---|-------------------------------------|
| BOILING RANGE (Deg F): 90 C - 304 | DENSITY: 12.24 lb/gl |
| VAPOR DENSITY: HEAVIER THAN AIR | SPECIFIC GRAVITY (H2O=1): 1.47 |
| COATING V.O.C.: 1.62 lb/gl | MATERIAL V.O.C.: 1.08 lb/gl |
| COATING V.O.C.: 194 g/l | MATERIAL V.O.C.: 130 g/l |
| SOLUBILITY IN WATER: Negligible | EVAPORATION RATE: SLOWER THAN ETHER |
| APPEARANCE AND ODOR: Gray liquid with mild odor | |

=====
SECTION IV - FIRE AND EXPLOSION HAZARD DATA
=====

FLASH POINT (Deg F): 1 METHOD USED: TOC
FLAMMABLE LIMITS IN AIR BY % VOLUME- LOWER: 0 UPPER: 12.8

EXTINGUISHING MEDIA: FOAM, CO2, DRY CHEMICAL

SPECIAL FIREFIGHTING PROCEDURES

Water may be used to cool closed containers to prevent pressure build-up. Wear self-contained breathing apparatus to avoid inhalation of smoke and fumes.

UNUSUAL FIRE AND EXPLOSION HAZARDS

Fire exposed containers may explode due to pressure build-up.

===== SECTION V - REACTIVITY DATA =====

STABILITY: STABLE

CONDITIONS TO AVOID

Heat and other sources of ignition

INCOMPATIBILITY (MATERIALS TO AVOID)

Strong oxidizing agents

HAZARDOUS DECOMPOSITION OR BYPRODUCTS

Thermal decomposition may yield carbon dioxide and/or carbon monoxide.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

===== SECTION VI - HEALTH HAZARD DATA =====

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Inhalation: May cause nasal and respiratory irritation.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Skin and eye contact: May cause irritation and discomfort to both.

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Skin absorption: May cause irritation.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Ingestion: May cause respiratory irritation, nausea and vomiting.

HEALTH HAZARDS (ACUTE AND CHRONIC)

Acute: May cause eye, nose and skin irritation, headache, nausea and vomiting.

Chronic: Prolonged and repeated contact may lead to central nervous system depression, pulmonary edema, liver and kidney damage.

CARCINOGENICITY: NTP CARCINOGEN: No IARC MONOGRAPHS: Yes OSHA REGULATED: No

This material contains ethylbenzene which is classified as "possibly carcinogenic to humans" (2B) by IARC. This material contains carbon black, which is classified as a possible carcinogen for humans (2B) by IARC.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

Pre-existing eye, skin and respiratory disorders may be aggravated.

EMERGENCY AND FIRST AID PROCEDURES

INHALATION: MOVE PERSON TO FRESH AIR. PROVIDE ARTIFICIAL RESPIRATION OR OXYGEN IF BREATHING IS DIFFICULT. **EYE & SKIN CONTACT:** FLUSH EYES IMMEDIATELY WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. WASH AFFECTED AREAS WITH SOAP AND WATER IMMEDIATELY. REMOVE CONTAMINATED CLOTHING. **INGESTION:** IF SWALLOWED, DO NOT INDUCE VOMITING. GET MEDICAL ATTENTION IMMEDIATELY.

===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED**

PROVIDE VENTILATION. LARGE SPILLS MAY BE SCOOPED UP. SMALL SPILLS MAY BE PICKED UP WITH ABSORBENT MATERIALS.

WASTE DISPOSAL METHOD

Incinerate or dispose of in accordance with local, state and federal regulations.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Store away from high temperatures, sparks and open flame. Keep containers tightly closed.

OTHER PRECAUTIONS

Do not take internally. Avoid prolonged contact.

===== SECTION VIII - CONTROL MEASURES =====**RESPIRATORY PROTECTION**

Use self-contained breathing apparatus where vapor concentration may be above the TLV limits. Where vapor does not exceed TLV limits, use NIOSH approved respirator.

VENTILATION

Adequate volume and pattern to keep air contaminant concentration below current applicable OSHA or ACGIH TLV limits.

PROTECTIVE GLOVES

Chemical resistant gloves

EYE PROTECTION

Chemical goggles

OTHER PROTECTIVE CLOTHING OR EQUIPMENT

Eye bath and safety shower

WORK/HYGIENIC PRACTICES

Wash hands thoroughly before eating or using the washroom. Smoke in smoking areas only.

===== SECTION IX - REGULATORY INFORMATION =====

CALIFORNIA PROPOSITION 65

This product contains a chemical known to the State of California to cause cancer.

Contains: Carbon Black - Ethylbenzene -

===== SECTION X - DISCLAIMER =====

The information contained herein is based on the data available to us and is believed to be correct. However, Pacific Coast Lacquer Co. makes no warranty expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof. Pacific Coast Lacquer Co. assumes no responsibility for injury from the use of the product described herein.