



VOC-COMPLIANT PRODUCTS

For Santa Barbara A.P.C.D., Rule 339

For Motor Vehicle and Mobile Equipment Coating Operations

Effective June 30, 2011

CLEAN AIR SOLVENTS (CAS) — Certified by SCAQMD (VOC Exempt)

Product:	NOVOC® COMPLIANT UNIVERSAL SOLVENT	COMPLIANT CLEANING SOLVENT	COMPLIANT WATERBORNE CLEANING SOLUTION
Number:	2040	4040	1720B
VOC as applied:	Exempt	Exempt	Exempt



SURFACE CLEANERS — VOC limit = 25 gm/ltr, .21 lb/gal

Product:	COMPLIANT CLEANING SOLVENT	ACETONE
Number:	8007	2010
VOC as applied:	0.21 lb/gallon	Exempt

PRE-TREATMENT COATING — VOC limit = 660 gm/ltr, 5.5 lb/gal

Product:	PRE-TREATMENT COATING
Number:	183A Black, 187A Green
Converter:	189B
Mix Ratio:	1:1
VOC as applied:	3.5 lb/gallon

PRIMER — VOC limit = 250 gm/ltr, 2.1 lb/gal

Product:	AQUAPRIMER	POLYPRIMER	POLYPRIMER 4:1	POLYPRIMER ULTRA-LOW VOC	HIGH BUILD SPEEDPRIME	SPEEDPRIME R.T.S.	2K EPOXY PRIME-N-SEAL	2K DTM ULTRA PRIMER	2K ACRYLIC URETHANE PRIMER
Number:	882 White 883 Gray 887 Buff	901 Gray 902 Red Oxide 903 Black 905 Buff 907 White	941 Gray Part A	931 Gray 932 Red Oxide 933 Black 935 Buff 937 White	913 Gray 922 Red Oxide	912 Gray	6701 Gray Part A 6702 Red Oxide 6703 Black 6707 White	6801 Gray Part A	6901 Gray Part A
Catalyst:			9498 Part B			6798 Part B	6898 Part B	6998 Part B	
Activator:		Liquid Hardener		Liquid Hardener					
Reducer:	Ready to spray	Ready to spray		Ready to Spray	Ready to spray	Ready to spray			
Mix Ratio:	N/A	2% L.H.	4:1	2% L.H.	N/A	N/A	2:1	3:1	3:1
VOC as applied:	2.1 lb/gallon	1.66 lb/gallon	1.66 lb/gallon	0.25 lb./gallon	2.1 lb/gallon	2.1 lb/gallon	2.1 lb/ gallon	2.1 lb/ gallon	2.1 lb/ gallon

PRIMER SEALERS — VOC limit = 250 gm/ltr, 2.1 lb/gal

Product:	SUPER SEAL RTS	2K CUSTOM SEALER	2K SEALER	2K EPOXY PRIME-N-SEAL	2K DTM ULTRA PRIMER	2K ACRYLIC URETHANE PRIMER
Number:	711	2671 Black Part A	6401 Gray Part A 6402 Red Oxide 6403 Black 6407 White 6498 Part B	6701 Gray Part A 6702 Red Oxide 6703 Black 6707 White 6798 Part B For Sealer 8025	6801 Gray Part A	6901 Gray Part A
Catalyst:		2679 Part B			6898 Part B	6998 Part B
Reducer:	Ready to Spray			For Sealer 8025	For Sealer 8025	For Sealer 8025
Mix Ratio:	N/A	4:1	4:1	2:1:1 Part A with Part B	3:1:1 Part A with Part B	3:1:1 Part A with Part B
VOC as applied:	2.1 lb/gallon	2.1 lb/gallon	2.1 lb/gallon	2.1 lb/gallon	2.1 lb/gallon	2.1 lb/gallon

SINGLE-STAGE COATINGS — VOC limit = 340 gm/ltr, 2.8 lb/gal

Product:	CHASSIS COATING	AQUAFLEX	FLAT BLACK	EUROCOAT	ENVIRO-FINISH
Number:	888 DTM Flat Black	889 Black	2703	2800 Series	6439 Series
Catalyst(s):			2798 Part B	2897 Catalyst for Completes or 2899 Catalyst	6340-98
Reducer:					8025, 8050, 4040, 8075
Mix Ratio:			4:1	4:1	1:1
VOC as applied:	0.8 lb/gallon	1.72 lb/gallon	2.42 lb/gallon	2.1 lb/gallon	2.8 lb/gallon

CLEAR COATINGS — VOC limit = 250 gm/ltr, 2.1 lb/gal

Product:	PREMIUM PRODUCTION EUROCLEAR	SATIN CLEAR URETHANE	SUPER PRO CLEAR	26 FLAT CLEAR	CLEAR ULTRA-LOW VOC
Number:	2400	2596 Satin Clear	2600	2613	2900
Catalyst(s):	2498	2597 Catalyst	2698 Multi-Panel or 2699 Spot and Panel	2630 Part B	2998 Part B
Reducer:	N/A		N/A		
Mix Ratio:	4:1	4:1	4:1	4:1	4:1
VOC as applied:	2.1 lb/gallon	1.0 lb./gallon	2.1 lb/gallon	2.1 lb/gallon	1.0 lb./gallon

Revised 06/15/11

