



VOC-COMPLIANT PRODUCTS

For South Coast (S.C.A.Q.M.D.) Rule 1151

For Motor Vehicle and Mobile Equipment Non-Assembly Line Coating Operations

Effective January 1, 2010

CLEAN AIR SOLVENTS (CAS) — Certified by SCAQMD (VOC Exempt)

Product: NOVOC® COMPLIANT UNIVERSAL SOLVENT	COMPLIANT CLEANING SOLVENT	COMPLIANT WATERBORNE CLEANING SOLUTION
Number: 2040	4040	1720B
VOC as applied: Exempt	Exempt	Exempt



SURFACE CLEANERS — VOC limit = 25 gm/ltr, .21 lb/gal

Product: AERO PREP SURFACE CLEANER (Aerosol)	MEDIUM SURFACE CLEANER (Aerosol)	COMPLIANT CLEANING SOLVENT	ACETONE
Number: 271	273	8007	2010
VOC as applied: MAX VOC – 100% by weight	MAX VOC – 100% by weight	0.21 lb/gallon	Exempt

PRE-TREATMENT COATING — VOC limit = 660 gm/ltr, 5.5 lb/gal

Product: PRE-TREATMENT COATING
Number: 183A Black, 187A Green
Converter: 189B
Mix Ratio: 1:1
VOC as applied: 3.5 lb/gallon

PRIMER — VOC limit = 250 gm/ltr, 2.1 lb/gal

Product: AQUAPRIMER	POLYPRIMER	POLYPRIMER 4:1	POLYPRIMER ULTRA-LOW VOC	HIGH BUILD SPEEDPRIME	SPEEDPRIME R.T.S.	2K EPOXY PRIME-N-SEAL	2K DTM ULTRA PRIMER	2K ACRYLIC URETHANE PRIMER
Number: 882 White 883 Gray 887 Buff	901 Gray 902 Red Oxide 903 Black 905 Buff 907 White	941 Gray Part A	931 Gray 932 Red Oxide 933 Black 935 Buff 937 White	913 Gray 922 Red Oxide	912 Gray	6701 Gray Part A 6702 Red Oxide 6703 Black 6707 White	6801 Gray Part A	6901 Gray Part A
Catalyst:		9498 Part B			6798 Part B	6898 Part B	6998 Part B	
Activator:	Liquid Hardener		Liquid Hardener					
Reducer:	Ready to spray		Ready to Spray	Ready to spray	Ready to spray			
Mix Ratio:	N/A	2% L.H.	4:1	2% L.H.	N/A	2:1	3:1	3:1
VOC as applied:	2.1 lb/gallon	1.66 lb/gallon	1.66 lb/gallon	0.25 lb./gallon	2.1 lb/gallon	2.1 lb/ gallon	2.1 lb/ gallon	2.1 lb/ gallon

PRIMER (Continued) — VOC limit = 250 gm/ltr, 2.1 lb/gal

Product: SUPER SEAL RTS	2K CUSTOM SEALER	2K SEALER	2K EPOXY PRIME-N-SEAL	2K DTM ULTRA PRIMER	2K ACRYLIC URETHANE PRIMER
Number: 711	2671 Black Part A	6401 Gray Part A	6701 Gray Part A 6702 Red Oxide 6703 Black, 6707 White	6801 Gray Part A	6901 Gray Part A
Catalyst:		2679 Part B	6498 Part B	6898 Part B	6998 Part B
Reducer:	Ready to Spray		6798 Part B	6898 Part B	6998 Part B
Mix Ratio:	N/A	4:1	4:1	3:1:1 Part A with Part B	3:1:1 Part A with Part B
VOC as applied:	2.1 lb/gallon	2.1 lb/gallon	2.1 lb/gallon	2.1 lb/gallon	2.1 lb/gallon

SINGLE-STAGE COATINGS — VOC limit = 340 gm/ltr, 2.8 lb/gal

Product: CHASSIS COATING	AQUAFLEX	FLAT BLACK	EUROCOAT	ENVIRO-FINISH
Number: 888 DTM Flat Black	889 Black	2703	2800 Series	6439 Series
Catalyst(s):		2798 Part B	2898 Multi-Panel or 2899 Spot and Panel	6340-98
Reducer:				8025, 8050, 4040, 8075
Mix Ratio:		4:1	4:1	1:1
VOC as applied:	0.8 lb/gallon	1.72 lb/gallon	2.42 lb/gallon	2.8 lb/gallon

CLEAR COATINGS — VOC limit = 250 gm/ltr, 2.1 lb/gal

Product: PREMIUM PRODUCTION EUROCLEAR	SUPER PRO CLEAR	26 FLAT CLEAR	CLEAR ULTRA-LOW VOC
Number: 2400	2600	2613	2900
Catalyst(s): 2498	2698 Multi-Panel or 2699 Spot and Panel	2630 Part B	2998 Part B
Reducer: N/A	N/A		
Mix Ratio: 4:1	4:1	4:1	4:1
VOC as applied: 2.1 lb/gallon	2.1 lb/gallon	2.1 lb/gallon	1.0 lb/gallon

Revised 01/01/10

