



# VOC-COMPLIANT PRODUCTS

For Ventura County A.P.C.D., Rule 74.18

For Motor Vehicle and Mobile Equipment Coating Operations

Effective January 1, 2010

## CLEAN AIR SOLVENTS (CAS) — Certified by SCAQMD (VOC Exempt)

<b>Product:</b> <i>NOVOC</i> <sup>®</sup> COMPLIANT UNIVERSAL SOLVENT	<b>COMPLIANT CLEANING SOLVENT</b>	<b>COMPLIANT WATERBORNE CLEANING SOLUTION</b>
<b>Number:</b> 2040	4040	1720B
<b>VOC as applied:</b> Exempt	Exempt	Exempt



## SURFACE CLEANERS — VOC limit = 25 gm/ltr, .21 lb/gal

<b>Product:</b> <b>AERO PREP SURFACE CLEANER (Aerosol)</b>	<b>MEDIUM SURFACE CLEANER (Aerosol)</b>	<b>COMPLIANT CLEANING SOLVENT</b>	<b>ACETONE</b>
<b>Number:</b> 271	273	8007	2010
<b>VOC as applied:</b> MAX VOC – 100% by weight	MAX VOC – 100% by weight	0.21 lb/gallon	Exempt

## PRE-TREATMENT COATING — VOC limit = 660 gm/ltr, 5.5 lb/gal

<b>Product:</b> <b>PRE-TREATMENT COATING</b>
<b>Number:</b> 183A Black, 187A Green
<b>Converter:</b> 189B
<b>Mix Ratio:</b> 1:1
<b>VOC as applied:</b> 3.5 lb/gallon

## PRIMER — VOC limit = 250 gm/ltr, 2.1 lb/gal

<b>Product:</b> <b>AQUAPRIMER</b>	<b>POLYPRIMER</b>	<b>POLYPRIMER 4:1</b>	<b>POLYPRIMER ULTRA-LOW VOC</b>	<b>HIGH BUILD SPEEDPRIME</b>	<b>SPEEDPRIME R.T.S.</b>	<b>2K EPOXY PRIME-N-SEAL</b>	<b>2K DTM ULTRA PRIMER</b>	<b>2K ACRYLIC URETHANE PRIMER</b>
<b>Number:</b> 882 White 883 Gray 887 Buff	901 Gray 902 Red Oxide 903 Black 905 Buff 907 White	941 Gray Part A	931 Gray 932 Red Oxide 933 Black 935 Buff 937 White	913 Gray 922 Red Oxide	912 Gray	6701 Gray Part A 6702 Red Oxide 6703 Black 6707 White	6801 Gray Part A	6901 Gray Part A
<b>Catalyst:</b>		9498 Part B			6798 Part B	6898 Part B	6998 Part B	
<b>Activator:</b>	Liquid Hardener		Liquid Hardener					
<b>Reducer:</b>	Ready to spray		Ready to spray	Ready to spray	Ready to spray			
<b>Mix Ratio:</b>	N/A	2% L.H.	4:1	2% L.H.	N/A	2:1	3:1	3:1
<b>VOC as applied:</b>	2.1 lb/gallon	1.66 lb/gallon	1.66 lb/gallon	0.25 lb./gallon	2.1 lb/gallon	2.1 lb/ gallon	2.1 lb/ gallon	2.1 lb/ gallon

## PRIMER SEALERS — VOC limit = 250 gm/ltr, 2.1 lb/gal

<b>Product:</b> <b>SUPER SEAL RTS</b>	<b>2K CUSTOM SEALER</b>	<b>2K SEALER</b>	<b>2K EPOXY PRIME-N-SEAL</b>	<b>2K DTM ULTRA PRIMER</b>	<b>2K ACRYLIC URETHANE PRIMER</b>
<b>Number:</b> 711	2671 Black Part A	6401 Gray Part A	6701 Gray Part A 6702 Red Oxide 6703 Black, 6707 White	6801 Gray Part A	6901 Gray Part A
<b>Catalyst:</b>		2679 Part B	6498 Part B	6898 Part B	6998 Part B
<b>Reducer:</b>	Ready to Spray		6798 Part B	6898 Part B	6998 Part B
<b>Mix Ratio:</b>	N/A	4:1	4:1	3:1:1 Part A with Part B	3:1:1 Part A with Part B
<b>VOC as applied:</b>	2.1 lb/gallon	2.1 lb/gallon	2.1 lb/gallon	2.1 lb/gallon	2.1 lb/gallon

## SINGLE-STAGE COATINGS — VOC limit = 340 gm/ltr, 2.8 lb/gal

<b>Product:</b> <b>CHASSIS COATING</b>	<b>AQUAFLEX</b>	<b>FLAT BLACK</b>	<b>EUROCOAT</b>	<b>ENVIRO-FINISH</b>
<b>Number:</b> 888 DTM Flat Black	889 Black	2703	2800 Series	6439 Series
<b>Catalyst(s):</b>		2798 Part B	2898 Multi-Panel or 2899 Spot and Panel	6340-98
<b>Reducer:</b>				8025, 8050, 4040, 8075
<b>Mix Ratio:</b>		4:1	4:1	1:1
<b>VOC as applied:</b>	0.8 lb/gallon	1.72 lb/gallon	2.42 lb/gallon	2.8 lb/gallon

## CLEAR COATINGS — VOC limit = 250 gm/ltr, 2.1 lb/gal

<b>Product:</b> <b>PREMIUM PRODUCTION EUROCLEAR</b>	<b>SUPER PRO CLEAR</b>	<b>26 FLAT CLEAR</b>	<b>CLEAR ULTRA-LOW VOC</b>
<b>Number:</b> 2400	2600	2613	2900
<b>Catalyst(s):</b> 2498	2698 Multi-Panel or 2699 Spot and Panel	2630 Part B	2998 Part B
<b>Reducer:</b> N/A	N/A		
<b>Mix Ratio:</b> 4:1	4:1	4:1	4:1
<b>VOC as applied:</b> 2.1 lb/gallon	2.1 lb/gallon	2.1 lb/gallon	1.0 lb/gallon

Revised 01/01/10

